

PLASTER FIXATIVE A



DESCRIPTION

PLASTER FIXATIVE A which is white in colour, is made of gypsum, mineral fillers and admixtures. It is sold in powder form, ready for mechanical mixing with water and then manual application.

PACKAGING

25 kg and 5 kg paper bags.

USES

Suitable for assembling/ setting of gypsum blocks, can be applied directly on the pieces to bond. It can also be used in conservation and rehabilitation interventions of interior coating of walls and ceilings, for repair of cracks and also as finishing coat. There is an excellent compatibility between this material and those normally used in ancient supports, which is why it has been widely used in this type of interventions.

WORKING TIME

About 2 to 3 hours, depending on the consistency of the paste and the conditions of application in work (temperature, ventilation, etc.).



APPLICATION

Add the product slowly to clean water in a clean receptacle, until saturated (typically around 14 kg of fixative for each litre of water).

Allow to rest for 2 to 3 minutes and then drill mix until a smooth and homogeneous paste is obtained.

Once mixed, spread onto the pieces to be glued in such a way that the adhesive later is not too thick.



WATER

The water used for the application should be potable and exempt of any impurities, and its temperature should be between 15 and 25 °C.



STORAGE

Store preferably in dry and reasonably ventilated conditions, maintaining the product in its original package.



ADDITIONAL INFORMATION

Do not add any other products to PLASTER FIXATIVE A. The product should be applied exactly as it is supplied in its original packaging.

The filler setting time can be greatly influenced by the way that the mix is prepared, the degree of cleanliness of the mixing receptacle and the water used. Any leftover filler from previous batches or cleaning water that has remained in the receptacle, even when in small quantities, can have a significant effect on the setting time of the next batch.

Do not use the material once it has begun to set.

Shelf Life - 6 to 9 months depending of the storage conditions.

Since the conditions of handling and application of our products are beyond our control, our liability is limited solely to the quality of same, not contemplating any anomaly arising its improper use.